



## Conference Chairman Unit TS-W103

### Embedded: full digital conference system embedded audio transmission software V2.25



#### Feature

- \* Adopt 48KHz sampling rate, providing clear and bright sound.
- \* Adopting advanced chip structure and unique processing algorithm, the microphone is turned on in 5 seconds only.
- \* With intelligent fault detection function, it prompts the user of AP faults, controller communication faults, low signal strength, etc.
- \* Support charging through the Type-C port, support smart state indicator, and 18W fast charging.
- \* Support SSID setting function.
- \* Support Chinese and English interface language switching, which can be set uniformly through PC software.
- \* Support the functions of speech stopwatch and speech timer.
- \* With the approval of the chairman, the delegate unit can apply to speak.
- \* With voice control function, it can turn on the microphone intelligently, and can adjust the voice sensitivity and set the shutdown time of the microphone via PC software.
- \* Support sign-in function: set and start the sign-in via PC software.
- \* Support voting function: five-key voting and three-key voting, flexible and convenient.
- \* Adopt 128-bit AES encryption technology, support WPA/WPA2 wireless security technology, prevent eavesdropping and unauthorized access, and provide higher confidentiality of the conference system.
- \* Adopt Wireless transmission technology, making wiring convenient and time-saving.
- \* The chairman has a priority function to turn off all delegate microphones that are speaking.
- \* Built-in lithium battery can support 14 hours of continuous speech.
- \* Adopt a 4.3-inch full-view IPS capacitive touch screen.
- \* The power switch is at the bottom of the microphone.

#### Specification

Model	TS-W103
Microphone type	Cardioid directional electret microphone
Frequency response	70Hz~12KHz
Sensitivity	-36±1.5dB
Maximum SPL	100dB(THD>3%)
SNR	>80dB(A)
Crosstalk	>70dB
Dynamic range	>80dB
THD	<0.1%
Maximum power consumption	3W
Power supply	18650 lithium battery
Charging method	Connect to the charging box via the TYPE-C interface
Color	Graphite gray
Sign in	Touch screen sign in
Screen	IPS screen
Size (L×W×H)	149*145*61(mm)
Installation method	Desktop
Wireless frequency range	5.15GHz~5.85GHz
Battery capacity	9600mAh
Microphone pole	380mm (black)
Weight	1Kg
Speech mode working hour	13H
Mixed mode working hour	14H